

Project No: MCC001901030201

Project: Final Remediation Investigation Geologist: M. Jackson

Client: AFCEE

Location: Site 24 - Vandenberg AFB

Northing: 639961.402

Borehole ID: HGL33(24MW13B)

Date: 11/15/2002

24-PMW-13 24-MW-13A

Checked By: D. Smith, R.G.

Ground Surface Elevation(ft msl): 460.14

Easting: 1768194.838

SUBSURFACE PROFILE				SAMPLE					
Depth	Symbol	Description	nscs	Elevation	Recovery %	Blow Counts	PID (ppm)	Water Level	Remarks
2		Fill	Fill	458					
4-		Poorly graded sand Moderate reddish brown, moist, soft, 100% medium grained sand							
6		<b>9</b>			95	7/9/15	0.8		·
8		i		450			·		
10-		Clay	C SC	449	100	8/8/24	0.9		
12		Pale yellowish brown, moist, soft, 100% / medium grained sand	30						
14-		Sandy clay		445					·
16-		Moderate yellowish brown, soft, moist, 80% clay, 40% sand	SP		_70	30/38/50	1.0		
18		Poorly graded sand Pale yellowish brown (90%) mottled with		1.10				•	Set temporary well at
20-		light brown (10%), soft, moist, 100% medium grained sand unit becomes saturated at 19.5'	sc	440	80	19/38/30	0.6	1	approximately 19'.
24		Sand with clay		435			'		
26		Pale yellowish brown (90%) mottled with light brown (10%), saturated to very	CL	700	95	24/18/17	0.8		
28		moist, soft, 85% sand, 15% clay							
30-		Clay with silt Pale yellowish brown mottled with dark	ML SM	430		20/00/00			
32		yellowish orange (15%), stiff, moist, moderate plasticity, 95% clay, 5% silt	SP		90	22/38/36	0.6		
34-		lense of clayey silt from 29.5' to 30' lense of sandy silt from 30' to 30.5'							
36		Poorly graded sand			90	15/04/45			
]		Pale yellowish brown, moist, soft, trace gravel (subangular, 5 mm x 3 mm)			90	15/24/15	0.9		
38~		lense of gravelly sand from 36.5' to 38.5'	SM	422					No intermediate zone water encountered.
40-					90	15/24/25	0.5		

Drilled By: Layne Christensen

Drill Method: Dual Tube Percussion

HydroGeoLogic, Inc. 4600 Northgate Blvd., Suite 207 Sacramento, CA 95834

Drilling Equipment: AP-1000

(916) 614-8770 FAX (916) 614-8775

Sampling Equipment: CA Mod Split Spoon

Boring Diameter: 10"

Total Depth Drilled: 69.5'

Sheet: 1 of 2



Project No: MCC001901030201

Project: Final Remediation Investigation Geologist: M. Jackson

Client: AFCEE

Location: Site 24 - Vandenberg AFB

Northing: 639961.402

Borehole ID: HGL33(24MW13B)

Date: 11/15/2002

Geologist: M. Jackson Checked By: D. Smith, R.G.

Ground Surface Elevation(ft msl): 460.14

Easting: 1768194.838

Well graded sand with gravel Pale yellowish brown and with iron oxide staining, moist, interstitial water at gravel contacts, 60% coarse grained sand, 30% gravel (variegated, angular to subrounded)  unit becomes very moist at 50' at 53' cobble zone encountered (6 mm x 3 mm x 2 mm, subrounded) 60% coarse sand, 25% gravel, 10% silt, 5% cobbles  Silty clay  Silty clay  Crossish gray, maist, pleatic,	SUBSURFACE PROFILE				SAMPLE			·			
Pale yellowish brown, moist, soft, medium sand, 95% medium grained sand, 5% silt, trace gravel (subrounded, 2 mm x 1 mm), lenses of clayey silt (3 mm thick)  Clayey silt Pale yellowish brown, moist, slightly stiff, 80% silt, 20% clay  Well graded sand with gravel Pale yellowish brown and with iron oxide staining, moist, interstitial water at gravel contacts, 60% coarse grained sand, 30% gravel (variegated, angular to subrounded)  Well graded sand with gravel Pale yellowish brown and with iron oxide staining, moist, interstitial water at gravel contacts, 60% coarse grained sand, 30% gravel (variegated, angular to subrounded)  unit becomes very moist at 50'  at 53' cobble zone encountered (6 mm x 3 mm x 2 mm, subrounded) 60% coarse sand, 25% gravel, 10% silt, 5% cobbles  Silty clay  Silty clay  Creative replication of the replication of th	Depth	Symbol	Description	nscs	Elevation		Blow Counts	PID (ppm)	Water Level	Remarks	
stiff, 60% clay, 40% silt  Gravelly sand Greenish gray, moist, 60% well graded sand, 30% gravel, 10% cobbles  Mudstone Black, slightly moist to moist, 1 cm bedding, weathered to 69.5'  76- 76- 76- 76- 78- 78- 78- 78- 78- 78- 78- 78- 78- 78	42 44 46 48 50 52 54 56 58 60 62 64 66 70 72 74	100 100 100 100 100 100 100 100 100 100	Pale yellowish brown, moist, soft, medium sand, 95% medium grained sand, 5% silt, trace gravel (subrounded, 2 mm x 1 mm), lenses of clayey silt (3 mm thick)  Clayey silt Pale yellowish brown, moist, slightly stiff, 80% silt, 20% clay  Well graded sand with gravel Pale yellowish brown and with iron oxide staining, moist, interstitial water at gravel contacts, 60% coarse grained sand, 30% gravel (variegated, angular to subrounded)  unit becomes very moist at 50'  at 53' cobble zone encountered (6 mm x 3 mm x 2 mm, subrounded) 60% coarse sand, 25% gravel, 10% silt, 5% cobbles  Silty clay Greenish gray, moist, plastic, slightly stiff, 60% clay, 40% silt  Gravelly sand Greenish gray, moist, 60% well graded sand, 30% gravel, 10% cobbles  Mudstone Black, slightly moist to moist, 1 cm	SM ML SW	397 396 395	90 80 70 70	19/47/46 18/50 for 5" 35/50/50	0.9		formation observed at 50  1420 Set deep well at 69.5'. 11/18/02 0725 Collect groundwater sample (HGL33-GW66).  Converted boring to deep well 24MW13B. Wells 24MPMW13 and	

Drilled By: Layne Christensen

Drill Method: Dual Tube Percussion

HydroGeoLogic, Inc. 4600 Northgate Blvd., Suite 207 Sacramento, CA 95834

Drilling Equipment: AP-1000

(916) 614-8770 FAX: (916) 614-8775

Sampling Equipment: CA Mod Split Spoon

Boring Diameter: 10"

Total Depth Drilled: 69.5'

Sheet: 2 of 2